



Safe Products

The SF range of **Self Adhesive Protection Foam**

SF Self Adhesive Protection Foam is a low-tack self adhesive foam protection which provides high-performance protection on glass, varnished wood, ceramics, plastics etc.



Specialist solutions for all your product needs

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam

High-performance protection

SF Self Adhesive Protection Foam has numerous benefits:

⇒ **Clean and aesthetic protection**

⇒ **Easy to apply**

⇒ **Perfectly removable**

Leaves no residue or adhesive marks. The glue can be chosen according to the surfaces needing protection.

⇒ **Economical**

Saves time and materials — replaces the need to use several products (adhesive & protective tapes, foams, bubble films...)

⇒ **Non-toxic**

⇒ **High performance**

A film combined with a foam — foam thickness adapted to the application

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk





Safe Products

SF Protection Foam V. standard protection

Self Adhesive Protection Foam:



SF Self Adhesive
Protection Foam



SF Self Adhesive
Protection Foam



SF Self Adhesive
Protection Foam



SF Self Adhesive
Protection Foam

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



Safe Products

SF Protection Foam v. standard protection

Standard protection:



Cardboard, wood &
adhesive tape



Film, bubble film &
adhesive tape



Peelable varnish

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam Range & Main Applications

REF	PEEL ON STEEL (N/25mm)	THICKNESS (µm)	LOG LENGTH (m)	APPLICATIONS	MAIN/REGULAR CUSTOMERS
SF7200	4.5	1100	50	Protection of plastics for the automotive industry. Sometimes permanent uses (Alveolaire).	Automotive & Aeronautic Industries
SF7222	4.5	2060	25	Protection of many surfaces: glass, ceramics, plastic, varnished woods, GRP in the Marine industry. Protection of plastics for the automotive industry. Sometimes permanent uses (Alveolaire).	Marine, Automotive & Aeronautic Industries
SF7210	2.5	1100	50	Protection of many surfaces: glass, ceramics, plastic, varnished woods (monocomposant).	Marine Industry
SF7220	2.5	2060	25	Same as SF7210 but with a thicker foam.	Marine & Furniture Industries
SF7211	1	1100	50	For very fragile surfaces: metalized surfaces, bi-composant varnishes, glass, metal, etc	Aeronautic Industry & Mirror Manufacture
SF7221	1	2060	25	Same as SF7211, but with a thicker foam.	Bodywork & Aeronautic Industry

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF


Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk





SF Self Adhesive Protection Foam Product construction

What is it?:



1. Foam

Foam composition: closed cells polyethylene (1 or 2mm thick)

2. Glue for lamination

Acrylic based

3. Support

50 μ polyethylene

4. Adhesive

Transparent acrylic
(3 different formulations)



Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk





SF Self Adhesive Protection Foam

High-performance protection

SF Self Adhesive Protection Foam specification and uses:

SF7210 & SF7211: 1mm PE foam laminated onto a PE film for protection of fragile surfaces - removable without residue and age resistant. SF7211 is a version with even less adhesion for very difficult surfaces, like hot stamped material, varnishes, PVC, etc.

SF7220 & SF7221: 2mm PE foam laminated with PE film for protection and spacing of fragile surfaces - removable without residue and age resistant. SF7221 is the less adhesive version of the 2mm foam.

SF7200 & SF7222: 1mm and 2mm PE foam laminated on PE film with higher adhesion, designed for curved and granular surfaces, for example.

SF Protec-tion Foam	Adhesive	Colour	Total thickness (µm)	Tensile strength (N/in.)	Elonga-tion at break (%)	Adhesion to steel (N/in.)	Tempera-ture re-sistance (°C)
SF7210	Acrylic	White	1100	>30	<200	2.5	60
SF7211	Acrylic	White	1100	>30	<200	1	60
SF7220	Acrylic	White	2060	>30	<200	2.5	60
SF7221	Acrylic	White	2060	>30	<200	1	60
SF7200	Acrylic	White	1100	>30	<200	4.5	60
SF7222	Acrylic	White	2060	>30	<200	4.5	60

Specialist solutions for all your product needs

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam SF7210

Short Description

Medium-low tack protection foam. Using SF7210 is economical — it saves time and materials with the highest level of protection.

PRODUCT DATA	
Carrier	Closed cell laminated polyethylene 1mm foam
Adhesive	Acrylic
Reinforcement film	50µ polyethylene film
Total thickness	1,1mm
Adhesion to steel	2,5 N/25mm
Tensile strength	> 30 N/25mm
Elongation at break	< 200%

Application

High performance protection on glass, ceramics, plastics, varnished wood, etc. Main application fields: boat building, furniture and glass industries. SF7210 is non-toxic and can be used in confined environments.

FEATURES	BENEFITS
Adhesive	Very easy application — does not require any additional tape or strip Removes easily and cleanly Leaves no adhesive residue Adhesive level ensures high security fixing Clean and aesthetic protection
Carrier	The PE foam ensures a very high level of protection against scratches and damages
PE reinforcement film	Provides high flexibility and high conformability even on difficult surfaces High bond between film and foam allows high tensile strength and easy removability

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam SF7220

Short Description

Medium-low tack protection foam: thicker version than SF7210. Using SF7220 is economical — it saves time and materials with the highest level of protection.

PRODUCT DATA	
Carrier	Closed cell laminated polyethylene 2mm foam
Adhesive	Acrylic
Reinforcement film	50µ polyethylene film
Total thickness	2.06mm
Adhesion to steel	2,5 N/25mm
Tensile strength	> 30 N/25mm
Elongation at break	< 200%

Application

High performance protection on glass, varnished wood, plastics, ceramics, etc. Main application fields are ship building, furniture and glass industries. SF7220 is non-toxic and can be used in confined environments.

FEATURES	BENEFITS
Adhesive	Very easy application—does not require any additional tape or strip Removes easily and cleanly Leaves no adhesive residue Adhesive level ensures high security bond even on difficult surfaces. Clean and aesthetic protection
Carrier	The PE foam ensures a very high level of protection against scratches and any damages
PE reinforcement film	Provides high flexibility and high conformability even on difficult surfaces High bond between film and foam allows high tensile strength and easy removability

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam SF7211

Short Description

Low tack protection foam. Using SF7211 is economical — it saves time and materials with the highest level of protection.

PRODUCT DATA	
Carrier	Closed cell laminated polyethylene 1mm foam
Adhesive	Acrylic
Reinforcement film	50 μ polyethylene film
Total thickness	1,1mm
Adhesion to steel	1 N/25mm
Tensile strength	> 30 N/25mm
Elongation at break	< 200%

Application

High performance protection on very difficult surfaces: metals, metalized surfaces, bi-component varnishes etc. Main application fields: furniture and glass industries and the marine industry (boat building). SF7211 is non-toxic and can be used in confined environments.

FEATURES	BENEFITS
Adhesive	Very easy application—does not require any additional tape or strip Removes easily and cleanly Leaves no adhesive residue Adhesive level ensures high security bond Clean and aesthetic protection
Carrier	The PE foam ensures a very high level of protection against scratches and any damages
PE reinforcement film	Provides high flexibility and high conformability even on difficult surfaces High bond between film and foam allows high tensile strength and easy removability

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam SF7221

Short Description

Low tack protection foam: thicker version than SF7211. Using SF7221 is economical — it saves time and materials with the highest level of protection.

PRODUCT DATA	
Carrier	Closed cell laminated polyethylene 2mm foam
Adhesive	Acrylic
Reinforcement film	50µ polyethylene film
Total thickness	2.06mm
Adhesion to steel	1 N/25mm
Tensile strength	> 30 N/25mm
Elongation at break	< 200%

Application

High performance protection on very difficult surfaces: metals, bi-component varnishes, metalized surfaces, etc. Main application fields are ship building, furniture and glass industries. SF7221 is non-toxic and can be used in confined environments.

FEATURES	BENEFITS
Adhesive	Very easy application—does not require any additional tape or strip Removes easily and cleanly Leaves no adhesive residue Adhesive level ensures high security bond even on difficult surfaces. Clean and aesthetic protection
Carrier	The PE foam ensures a very high level of protection against scratches and any damages
PE reinforcement film	Provides high flexibility and high conformability even on difficult surfaces High bond between film and foam allows high tensile strength and easy removability

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam SF7200

Short Description

High tack protection foam. Using SF7200 is economical — it saves time and materials with the highest level of protection.

PRODUCT DATA	
Carrier	Closed cell laminated polyethylene 1mm foam
Adhesive	Acrylic
Reinforcement film	50µ polyethylene film
Total thickness	1,1mm
Adhesion to steel	4 N/25mm
Tensile strength	> 30 N/25mm
Elongation at break	< 200%

Application

High performance protection on plastics. Main application area is the automotive industry. SF7200 is non-toxic and can be used in confined environments. SF7200 ensures double protection both during handling (dirt and marks) and transport (shock proof).

FEATURES	BENEFITS
Adhesive	Very easy application—does not require any additional tape or strip Removes easily and cleanly Leaves no adhesive residue Adhesive level ensures high security bond even on difficult surfaces Clean and aesthetic protection
Carrier	The PE foam ensures a very high level of protection against scratches and any damages
PE reinforcement film	Provides high flexibility and high conformability even on difficult surfaces High bond between film and foam allows high tensile strength and easy removability

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk



SF Self Adhesive Protection Foam SF7222

Short Description

High tack protection foam. Using SF7222 is economical — it saves time and materials with the highest level of protection.

PRODUCT DATA	
Carrier	Closed cell laminated polyethylene 2mm foam
Adhesive	Acrylic
Reinforcement film	50µ polyethylene film
Total thickness	2,06mm
Adhesion to steel	4 N/25mm
Tensile strength	> 30 N/25mm
Elongation at break	< 200%

Application

High performance protection on plastics. Main application areas are the automotive and marine industries. SF7222 is non-toxic and can be used in confined environments. SF7222 ensures double protection both during handling (dirt and marks) and transport (shock proof).

FEATURES	BENEFITS
Adhesive	Very easy application—does not require any additional tape or strip Removes easily and cleanly Leaves no adhesive residue Adhesive level ensures high security bond even on difficult surfaces
Carrier	The PE foam ensures a very high level of protection against scratches and any damages
PE reinforcement film	Provides high flexibility and high conformability even on difficult surfaces High bond between film and foam allows high tensile strength and easy removability

Safe Products

Safe Products Ltd
Wireless House
Wireless Hill
South Luffenham
Rutland LE15 8NF

Phone: 01780 721460
Fax: 01780 721644
E-mail: sales@safeproductsltd.co.uk
www.safeproductsltd.co.uk